



**Get 25 Kgms. of Lithium for each ton of lithium salt
(SCO) - SODIUM CHLORIDE (LITHIUM SALT)**

You hereby receive the following Soft Corporate Offer (SCO), on behalf of the final seller to confirm and sell the following product and enter into a sales contract we are ready and willing and able to produce, process, sell and deliver

The goods this document is provided with the following terms and conditions:

PRODUCT: Industrial salt (lithium salt)

SOURCE: Chile

QUALITY: 2,5% min lithium / 25Kg per MT

QUANTITY: 10,000 MT first month / of the second month 50,000 MT

MONTHLY PRODUCTION: From 50,000 to 150.000 tons per month (+/- 10%)

GRANULOMETRY: Standard

SHIPMENTS: Bulk bags in the ship's warehouse

INCOTERMS: FOB

PRICE: \$ 800 USD per MT of Lithium Salt



PAYMENT SYSTEM: DLC / MT 720 Transferable, Confirmed, at sight, Irrevocable.

Or 30% advance 70% paid against BL


CERTIFICATIONS: SGS, Alex Stewart or Equivalent

CONTRACT PERIOD: 1 year to 5 Years, automatically renewable.

ATTACHMENTS

		INFORME DE ANÁLISIS QUÍMICO			
DATOS INTERNOS		DATOS TÉCNICOS			
Certificado N°	INFO1019-0682	Solicitud	Técnica	Método	L. Detección
Emitido por	Geosassay Ltda.	ICP 33 AR	ICP	Digestión Agua Regia	—
Dirección	Av. America Vesputio 1273; Pudahuel; Stgo.				
Fono	+56-2-27607500				
Web	www.Geosassay.cl				
e-mail	manuel.diaz@geosassay.cl				
Fecha de Informe	10-11-2022				
N° Páginas	3				
DATOS CUENTE					
Identificación Cliente					
Nombre Contacto					
Cargo Contacto					
Proyecto					
Envío					
e-mail					
DATOS SERVIDO					
Cantidad de Muestras		2			
N° Análisis ICP 33AR		2			
 Manuel Diaz Geosassay Ltda.					

		Resultados de ICP-OES																																
Unidad	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L									
Unidad	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L									
1	Salvadora V4	<1	<0.05	0.24	10.2	0.81	<10	<20	<0.05	<10	<10	<10	<10	<10	0.05	<20	<2	<0.1	3.37	<0.01	0.11	6.94	<11	<50	<50	<0.01	<50	<10	<0.1	<50	111	<20	<20	<20
1	Salvadora V4	<1	<0.05	2.84	28.2	0.89	<10	<20	<0.05	<10	<10	<10	<10	<10	0.05	<20	<2	<0.1	3.99	<0.01	0.1	0.24	<11	<50	<50	<0.01	<50	<10	<0.1	<50	22	<20	<20	<20

		Controles de ICP-OES																																	
Unidad	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L
Unidad	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L	g/L
1	272	2	1.93	58	51	79	-10	-20	9.15	-10	-10	-10	19	1.5	-20	-2	3.4	-50	0.1	289	-15	0.34	13.0	505	28.0	5.1	-50	244	0.06	-50	51	-20	49	-20	
2	97D-9020	-1	2.20	60	-10	275	-10	-20	1.00	-10	15	51	7222	4.1	-30	-2	1.2	-50	1.2	347	235	0.10	34.0	960	-20	0.8	-50	59	0.21	-50	57	-20	59	-20	
3	8K	-1	-0.05	-50	-10	-50	-10	-20	-0.05	-10	-10	-10	-10	-0.1	-30	-2	-0.1	-50	-0.1	-10	-10	-0.05	-10	-50	-20	-0.1	-50	-10	-0.05	-50	-5	-20	-20	-20	
4	288	-1	0.15	-50	45	-50	-10	-20	8.25	-10	-10	-10	-10	-0.1	-30	-2	-0.1	-50	-0.1	-10	-10	-0.05	-10	-50	-20	0.0	-50	990	-0.05	-50	-5	-20	-20	-20	
5	97D-822	-1	2.74	-50	38	75	-10	-20	0.34	-10	30	44	1971	4.8	-30	-2	3.4	-50	1.3	795	-15	0.00	35.0	660	58.0	0.4	-50	15	0.09	-50	30	-20	213	24	
6	300	1	0.74	-50	55	-50	-10	-20	0.00	-10	-10	15	15	0.7	-30	-2	3.2	-50	-0.1	362	-15	0.20	10.0	291	-20	>10	-50	537	-0.05	-50	17	-20	23	21	
7	8K	-1	-0.05	-50	-10	-50	-10	-20	-0.05	-10	-10	-10	-10	-0.1	-30	-2	-0.1	-50	-0.1	-10	-10	-0.05	-10	-50	-20	-0.1	-50	-10	-0.05	-50	-5	-20	-20	-20	
8	316	-1	1.80	-50	-10	143	-10	-20	1.72	-10	-10	17	62	1.6	-30	-2	3.2	-50	0.1	201	-15	0.83	-10	593	33.0	0.0	-50	294	-0.05	-50	32	-20	20	-20	
9	97D-826	-1	2.84	-50	-10	56	-10	-20	0.32	-10	24	23	351	5.4	-30	-2	3.0	-50	1.4	819	-15	0.07	34.0	623	35.0	1.1	-50	14	0.07	-50	30	-20	37	23	

For the extraction of Lithium, the DLE method is used, which is a proven technology, with projects established and in production in China and South America. In a DLE operation, the brine is pumped to a processing unit where a resin or adsorbent is used to extract only the lithium from the brine, while the spent brine is reinjected into the basin's aquifers.

The reinjection of brine into the aquifer is a crucial environmental differentiator between the DLE process adopted by Cleantech and other lithium producers using evaporation pond processes.

If you accept this offer, please return signed with your company details, and we will send you an FCO or SPA if you send us an ICPO first. Thanks for trusting us.

Name

Company

Name

Email

Phone

Address